

# HARD ALLOY TUBE & PIPE



## DRAWN SEAMLESS ALUMINUM TUBE CAPABILITIES

STANDARD ALLOYS & TEMPER								
2024	3003	5052	6061	6063	7050	7068	7075	K749A
O	O	O	O	T6	O	O	O	T6
T3	H12	H32	T4	T831	T6	T6	T6	
	H14	H34	T6	T832	T76		T76	
							T73	

STANDARD ALLOYS & SPECIFICATIONS*								
2024	3003	5052	6061	6063	7050	7068	7075	K749A
AMS 4086	ASTM B210	AMS 4069	AMS 4079	ASTM B483			ASTM B 210	
AMS 4087	AMS-T-700/2	AMS4070	AMS 4080	ASTM B241			AMS-T-700/7	
AMS 4088	AMS4065	AMS4071	AMS4081	MIL-P-25995				
AMS-T-700/3	AMS4067	ASTM B 210	AMS 4082					
ASTM B210	ASME SB234	ASME SB210	AMS 4083					
		ASTM B 234	ASME SB210					
		ASTM B 483	ASTM B 210					
		AMS-T-700/4	ASTM B 234					
			ASTM B 241					
			ASTM B 483					
			AMS-T-700/6					
			MIL-P25995					
			AMS-T-7081					

DIMENSIONAL RANGES					
		Wall			
Inches	Millimeters	Inches	Millimeters	Feet	Meters
0.125 - 3.00	3.18 - 76.20	0.018 - .250	0.46 - 6.35	0.50 - 20.00	0.15 - 8.00

### Notes

Some specifications are no longer available but are provided for reference.

Press minimums vary from 300 - 1,000 lbs. Call for availability.

# HARD ALLOY TUBE & PIPE



## EXTRUDED SEAMLESS ALUMINUM TUBE CAPABILITIES

STANDARD ALLOYS & TEMPER					
2024	5052	7005	7046	7050	7075
O	O	F	O	F	O
T3					T6
T3511					T6511

STANDARD ALLOYS & SPECIFICATIONS					
2024	5052	7005	7046	7050	7075
ASTM B241	ASTM B241	ASTM B221			ASTM B241
ASTM B221	ASTM B221				ASTM B221
AMS 4152	ASME SB241				AMS 4154
ASME SB221					AMS-QQ-A-200/11
AMS-QQ-A-200/3					

DIMENSIONAL RANGES - ALLOYS 2024, 5052, 7050, 7075				
Wall Thickness (in.)	Outside Diameter (in.)			
	1.625/2.249	2.250/2.999	3.000/3.999	4.000/4.500
0.110 - 0.180	This area identifies available Extruded Seamless Aluminum Tube dimensional ranges.			
0.181 - 0.280				
0.281 - 0.374				
0.375 - 0.499				

DIMENSIONAL RANGES - ALLOYS 7005, 7046				
Wall Thickness (in.)	Outside Diameter (in.)			
	1.050/1.500	1.501/1.999	2.000/2.999	3.000/3.999
0.088 - 0.129	This area identifies available Extruded Seamless Aluminum Tube dimensional ranges.			
0.130 - 0.180				
0.181 - 0.218				
0.219 - 0.280				
0.281 - 0.374				
0.375 - 0.499				
0.500 - 0.749				

**Notes**

Press minimums vary from 300 - 1,000 lbs. Call for availability.